



## Communication & Control

### Telephone, Headset Cables

PE/PVC

UL Type CM, UL AWM 2092, 2093, 2094, CSA CMG FT4, RoHS Compliant, 300 Volt

#### CHARACTERISTICS

##### TELEPHONE STATION CABLE

#### OPERATING TEMPERATURE

- -20°C to 75°C – CM
- 60°C – AWM

#### VOLTAGE RATING

- 300 Volt

#### COLOUR DESCRIPTION

- Colour code: 1-Red, 2-Green, 3-Yellow, 4-Black
- Jacket colour: beige

#### PRODUCT DESCRIPTION

- Conductor: solid bare copper
- Insulation: colour-coded polyethylene (PE)

#### SPECIFICATIONS

- UL Type CM
- UL AWM 2092, 2093, 2094
- CSA CMG FT4
- Passes UL VW-1 flame test
- RoHS Compliant
- UL Listed, CSA Certified

#### Applications: Headset Cable

- Designed for two channel transmission on audio-visual education, language laboratories, etc.

#### CHARACTERISTICS

#### OPERATING TEMPERATURE

- -20°C to 80°C

#### VOLTAGE RATING

- 200 Volt

#### COLOUR DESCRIPTION

- Colour code: red, clear
- Jacket colour: gray

#### PRODUCT DESCRIPTION

- Conductor: Stranded mixture of tinned copper and copper-clad steel
- Insulation: colour-coded polyethylene (PE)
- Shield: individually spiral wrapped tinned copper
- Jacket: PVC

#### AVAILABILITY

- 1000 ft (305m) put-ups
- Consult for Alpha Qwik-Reel® payout package availability

#### Specification Information

##### TELEPHONE STATION CABLE 80°C PE/PVC

Alpha Part No.	No. of Cond.	Jacket Thickness		Diameter	
		Inches	mm	Inches	mm
1202	2	0.020	0.50	0.15	3.9
1203	3	0.020	0.50	0.16	4.1
1204	4	0.022	0.55	0.18	4.7

#### Specification Information

##### HEADSET CABLE 80°C PE/PVC

25 AWG (0.18mm <sup>2</sup> 0, 7/33 (7x0.18mm), Insulation Thickness: 0.017" (0.43mm)					
Alpha Part No.	No. of Cond.	Jacket Thickness		Diameter	
		Inches	mm	Inches	mm
1985	2	0.020	0.50	0.108 x 0.215	2.74 x 5.46

