



Communication & Control

Multiconductor, braid shield

Rubber
600 Volt

CHARACTERISTICS

OPERATING TEMPERATURE

- -20°C to 60°C

VOLTAGE RATING

- 600 Volt

COLOUR DESCRIPTION

- Colour Code: Chart H
- Jacket Color: black

PRODUCT DESCRIPTION

- Conductor: Stranded tinned copper
- Insulation: color-coded rubber
- Wrap: clear polyester
- Shield: braided tinned copper (85% coverage)
- Jacket: Rubber

AVAILABILITY

- 100 ft (30.5m), 500 ft (152m),
1000 ft (305m) put-ups

Specification Information



20 AWG (0.52mm ²), 26/34 (26x0.16mm), Insulation Thickness: 0.020" (0.51mm)							
Alpha Part No	No. of Cond.	Conductor		Jacket Thickness		Diameter	
		AWG	Strand	Inches	mm	Inches	mm
1250	2	20	26/34	0.045	1.14	0.28	7.1
1251	3	20	26/34	0.045	1.14	0.29	7.4
1252	4	20	26/34	0.045	1.14	0.31	7.9
1254	6	20	26/34	0.045	1.14	0.36	9.2
1255	7	20	26/34	0.045	1.14	0.36	9.2
1255/8	8	20	26/34	0.045	1.14	0.39	9.9
1255/10	10	20	26/34	0.045	1.14	0.43	10.9
1255/12	12	20	26/34	0.065	1.65	0.48	12.1

