



## Communication & Control

Multiconductor, unshielded

Rubber

600 Volt

### CHARACTERISTICS

#### OPERATING TEMPERATURE

- -20°C to 60°C

#### VOLTAGE RATING

- 600 Volt

#### COLOUR DESCRIPTION

- Colour Code: Chart H
- Jacket Color: black

#### PRODUCT DESCRIPTION

- Conductor: Stranded tinned copper
- Insulation: Colour-coded rubber
- Wrap: clear polyester
- Jacket: rubber

#### AVAILABILITY

- 100 ft (30.5m), 500 ft (152m),  
1000 ft (305m) put-ups

### Specification Information



20 AWG (0.50mm <sup>2</sup> ), 26/34 (26x0.16mm), Insulation Thickness: 0.020" (0.50mm)						
Alpha Part No	No. of Cond.	Jacket Thickness		Diameter		
		Inches	mm	Inches	mm	
1244	2	0.035	0.89	0.23	5.8	
1245	3	0.035	0.89	0.24	6.1	
1246	4	0.035	0.89	0.26	6.6	
1247/6	6	0.035	0.89	0.31	7.9	
1247/10	10	0.035	0.89	0.37	9.4	
1247/12	12	0.035	0.89	0.39	9.9	
1247/15	15	0.035	0.89	0.43	10.9	

