



Communication & Control

Multiconductor, braid shield

Rubber/Neoprene Microphone Cables

Specification Information



Alpha Part No.	No. of Cond.	Conductor		Insulation Thickness		Jacket Thickness		Diameter		Type of Jacket	◆Nominal Cap. pF/ft.
		AWG	Strand	Inches	mm	Inches	mm	Inches	mm		
1448/20	2	20	26/34	0.020	0.50	0.040	1.02	0.26	6.6	Rubber	68
1448/18	2	18	41/34	0.020	0.50	0.035	0.88	0.29	7.4	Neoprene	78
1448/16	2	16	65/34	0.025	0.63	0.035	0.088	0.34	8.5	Neoprene	82

◆ between one conductor and remaining conductors (if any) connected to shield

Applications

- All low impedance microphones

CHARACTERISTICS

OPERATING TEMPERATURE

- -20°C to 60°C

COLOUR DESCRIPTION

- Colour Code: 1-White, 2-Black
- Jacket Color: 1771 – black

PRODUCT DESCRIPTION

- Conductor: stranded tinned copper
- Insulation: rubber
- Wrap: overall cotton
- Shield: braided tinned copper (85% coverage)
- Jacket: rubber or neoprene

AVAILABILITY

- 1000 ft (305m) put-ups

